

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Industrial luminaire

Name and address of the applicant

TREVOS, a.s.
Nová Ves 34, 511 01 Turnov, Czech Republic

Name and address of the manufacturer

TREVOS, a.s.
Nová Ves 34, 511 01 Turnov, Czech Republic

Name and address of the factory

TREVOS, a.s.
Nová Ves 34, 511 01 Turnov, Czech Republic

Note: When more than one factory, please report on page 2

 Additional Information on page 2

Ratings and principal characteristics

220-240 V, 50/60 Hz, IP66/IP69, ta=45 °C or 50 °C

Trademark / Brand (if any)

TREVOS

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

PRIMA 1.aft bb cc dddd/eee fff gg
NANOTTICA 1.2ft, 1.4ft, 1.5 ft

Additional information (if necessary may also be reported on page 2)

Amendment M1: 30. 11. 2022

Reason for change:

To the body of the luminaire added translucent diffusor as an alternative variant, the construction of the luminaire is same as before.

Amendment M2: 23. 10. 2023

Reason for change:

A new type series of PRIMA luminaires has been added, which is constructively and technically identical to the model series of NANOTTICA luminaires, but only in TRS, VP or basic version without denotation (see above).

 Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60598-2-1:2020,
IEC 60598-1:2020

As shown in the Test Report Ref. No. which forms part of this Certificate

210466-01/01 of: 30.06.2021, 210466-01/01 M1 of: 30.11.2022,
210466-01/01-M2 of: 23.10.2023

This CB Test Certificate is issued by the National Certification Body

Elektrotechnický zkušební ústav, s. p.
Pod lisem 129/2, 182 00 Praha 8, Troja
Czech Republic

Date: 07.07.2021 corr. 02.11.2023

Miroslav Sedláček
Certification and Inspection Manager

PRIMA 1.aft bb cc dddd/eee fff gg**a** = length 2/4/5 feet (ft)**bb** = type series - **TRS**- indirect lighting (clear base),
VP- outdoor (added ventilation sticke Gore),
base version without denotation**cc** = material – PC/PC, PCc/PC, ABS/AC, ABSc/AC , ABS/ABS, ABSc/ABS**dddd** = lumen flux 1300 up to 8000 lm**eee** = CRI and CCT 827 to 865 and 927 to 965**fff** = **base version without denotation** or **DALI** (version with digital dimmable driver DALI)**gg** = "1F" = light fitting with 1-phase 3 core through-wiring

or

"3F" = light fitting with 3-phase 5 core through-wiring

or

" " = light fitting without through-wiring

NANOTTICA 1.xft bb cc dddd/eee fff gg**X** = length 2/4/5 feet (ft)**bb** = type series - **WB**- widebeam, **NB**- narrowbeam, **TRS**- indirect lighting (clear base),
VP- outdoor (added ventilation sticke Gore), **ASY** – asymmetrical,
VWB- ultra widebeam, **TL**-translucent (translucent diffusor)
base version without denotation**cc** = material – PC/PC, PCc/PC, ABS/AC, ABSc/AC , ABS/ABS, ABSc/ABS**dddd** = lumen flux 1300 up to 8000 lm**eee** = CRI and CCT 827 to 865 and 927 to 965**fff** = **base version without denotation** or **DALI** (version with digital dimmable driver DALI)**gg** = "1F" = light fitting with 1-phase 3 core through-wiring

or

"3F" = light fitting with 3-phase 5 core through-wiring

or

" " = light fitting without through-wiring

Additional information (if necessary)Elektrotechnický zkušební ústav, s. p.
Pod lisem 129/2, 182 00 Praha 8, Troja
Czech Republic**Date:** 07.07.2021 corr. 02.11.2023

Signature:

Miroslav Sedláček
Certification and Inspection Manager